



China 6206 Bearing Supplier



6003 2RS Zz SKF/NACHI/NTN/NSK/Timken/Koyo Interchange Bearing

Bearing No. 6003

6003 Bearing 2D drawings and 3D CAD models

Size	17x35x10 mm
Bore Diameter	17 mm
Outer Diameter	35 mm
Width	10 mm
d	17 mm
D	35 mm
B	10 mm
C	10 mm
r min.	0.3 mm
da min.	19 mm
Da max.	33 mm
ra max.	0.3 mm
Weight	0.039 Kg
Basic dynamic load rating (C)	6 kN
Basic static load rating (C0)	3,25 kN
(Grease) Lubrication Speed	20000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0



China 6206 Bearing Supplier

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	17MM Bore; 35MM Outside Diameter; 10MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nachiamerica.com
Outside Diameter	1.378 Inch 35 Millimeter
Bore	0.669 Inch 17 Millimeter
Outer Race Width	0.394 Inch 10 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	17 mm
Width	10 mm
Fillet Radius/Chamfer	0.3 mm
Dynamic Load Rating	6,000 N



China 6206 Bearing Supplier

Static Load Rating	3,250 N
Limiting Speed - Grease	22,000 rpm
Limiting Speed - Oil	26,000 rpm
Factor f_0	14.3
Radial Clearance	0.003 to 0.018 mm
da (min)	19 mm
Da (max)	33 mm
ra (max)	0.3 mm